

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
4 January 2001 (04.01.2001)

PCT

(10) International Publication Number
WO 01/00427 A2

- (51) International Patent Classification⁷: **B60C**
- (21) International Application Number: PCT/US99/29527
- (22) International Filing Date:
14 December 1999 (14.12.1999)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
29/106,959 24 June 1999 (24.06.1999) US
- (71) Applicant (for all designated States except US): **THE GOODYEAR TIRE & RUBBER COMPANY** [US/US]; Dept. 823, 1144 East Market Street, Akron, OH 44316-0001 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **WELBES, Paul** [LU/LU]; 38, rue Principale, L-9184 Schrodweiler (LU). **LARDO, Claude** [BE/LU]; 19, rue St-Hubert, L-1744 Luxembourg (LU).
- (74) Agent: **KING, David, L.**; The Goodyear Tire & Rubber Company, Dept. 823, 1144 East Market Street, Akron, OH 44316-0001 (US).
- (81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— Without international search report and to be republished upon receipt of that report.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TREAD FOR A LIGHT TRUCK OR AUTOMOBILE TIRE



(57) Abstract: A tread (12) for a light truck or automobile tire (10) has a continuous rib (30, 32) between an adjacent piece of circumferentially continuous grooves (20, 22, 24). The tread (12) has a plurality of hook-shaped semi-blind grooves (40) originating from the circumferentially continuous grooves (20, 22, 24). Each rib (30, 32) has two rows of circumferentially spaced hook-shaped semi-blind grooves (40).

WO 01/00427 A2

FOOT-408700